

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 08-250083  
 (43)Date of publication of application : 27. 09. 1996

(51) Int. Cl. H01M 2/06  
 H01M 2/30


(21)Application number : 07-074559 (71)Applicant : KEIHIN RIKA KOGYO:KK  
 A T BATTERY:KK  
 (22)Date of filing : 07. 03. 1995 (72)Inventor : SASE TOSHI  
 YAMASHITA MASATAKA

## (54) NONAQUEOUS SYSTEM BATTERY

## (57) Abstract:

PURPOSE: To provide a battery excellent in air-tightness and insulation, by charging between a hole part drilled in a sheathing vessel and a periphery of inserted electrode pin with a seal member formed of synthetic resin material having non-reversible thermal expansion character.

CONSTITUTION: Between the periphery of an electrode pin 4 inserted into a hole part 2 drilled in a sheathing vessel 1 of a battery and the hole part 2, a seal member 3 formed of synthetic resin material having non-reversible thermal expansion character is interposed, to heat the member 3 expanded. The member 3 uses a thermal expansion tube of forming ethylene tetrafluoroethylene-perphloroalkyl vinyl ether copolymer resin, tetrafluoroethylene-propylene hexafluoride copolymer resin, etc., into a particular molecular structure. In this way, a clearance between the hole part 2 and the pin 4 is eliminated, to obtain a surely air-tight seal condition.



## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

**BEST AVAILABLE COPY**